

Identification of Substance & Company

Product

Product name Maxlife Super Heavy Duty Battery

Product code NA

HSNO approval exempt - manufactured article
Approval description exempt - manufactured article

UN number NA
Proper Shipping Name NA
Packaging group NA
Hazchem code NA
Uses Battery

Company Details

Company P.K. Global Limited
Address 136 Motu Road

RD1 Kumeu Auckland 0891 New Zealand

Telephone 0064 9 412 5136 **Fax** 0064 9 412 5135

Emergency Telephone Number: 0800-764 766

2. Hazard Identification

Approval

Manufactured article: Batteries are considered to be manufactured articles and are not, therefore, covered by the HSNO Act. Under normal circumstances, a battery is sealed and the substance is not expected to be released.

The following classification and hazards are associated with the contents of an open battery.

Classes Hazard Statements

6.1E (oral) H303 - May be harmful if swallowed

6.1D (inhalation) H332 - Harmful if inhaled.

8.2C H314 - Causes severe skin burns and eye damage.

8.3A H318 - Causes serious eye damage.

6.8B H361 - Suspected of damaging fertility or the unborn child.

6.8C H362 - May cause harm to breast-fed children.

6.9A H372 - Causes damage to organs through prolonged or repeated exposure.

9.1A H410 - Very toxic to aquatic life with long lasting effects.

9.3C H433 - Harmful to terrestrial vertebrates. **SYMBOLS**

DANGER



Other Classifications

Swallowing an intact battery can be harmful. If intact battery is swallowed, seek medical attention immediately.

If batteries are place in a fire, they may rupture and the contents may intensify the fire.



Precautionary Statements – these apply to the contents of an opened battery.

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe fume/vapours.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

P281 - Use personal protective equipment as required.

P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P363 - Wash contaminated clothing before reuse.

P310 - Immediately call a POISON CENTRE or doctor/physician.

P304+P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTRE or doctor/physician.

P308+P313 - IF exposed or concerned: Get medical advice/ attention.

P309+P311 - IF exposed or if you feel unwell: Call a POISON CENTRE or doctor/physician.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Concentration
Carbon black	1333-86-4	4-6%
Manganese Dioxide	1313-13-9	26-30%
Zinc	7440-66-6	27-30%
Zinc chloride	7646-85-7	5-8%
Graphite	7782-42-5	5-8%
Water	7732-18-5	14-18%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4 First Δid

General Information

Decempeded first oid

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service). IF exposed or concerned: Get medical advice/ attention.

Pondy appear to rupping water is required. Appearible evoluted is required

facilities	Ready access to running water is required. Accessible eyewash is required.
Exposure	
Swallowed Eye contact	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Contact a doctor immediately. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.
Inhaled	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Advice to Doctor	

Page 2 of 7 February 2020

Treat symptomatically

Product Name: Maxlife Super Heavy Duty Battery



5. Firefighting Measures

Fire and explosion hazards: Batteries may present a hazard if exposed to a fire. Batteries can rupture in a fire and

release contents as toxic fumes or vapours. Manganese dioxide and zinc are oxidisers

and can intensify a fire.

Suitable extinguishing

substances:

Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or alcohol resistant foam. Keep intact batteries cool if exposed to a fire to prevent rupture.

Unknown.

NA

Unsuitable extinguishing

substances:

Batteries may emit toxic fumes and vapours in a fire.

Products of combustion: Batte
Protective equipment: Self-c

Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat

and eye protection.

Hazchem code:

6. Accidental Release Measures

Containment There is no current legal requirement for containment of this product. It is a

manufactured article.

Emergency procedures for release of contents of a battery

In the event that a battery is damaged and the content is released:

Wear protective equipment to prevent skin, eye and respiratory exposure. (see section 8 for details). Contain leakage using sand, earth or vermiculite. Collect and seal in properly

labelled containers for disposal.

Emergency procedures (intact

batteries)

In the event of spillage of a large number of batteries (>100kg) alert the fire brigade to

location and give brief description of hazard. Stop the source of the leak, if safe to do so.

Prevent by whatever means possible any batteries from entering drains, sewers, or water

courses. (If this occurs contact your regional council immediately).

Disposal Collect recoverable material into labelled containers for recycling or salvage. Recycle

containers wherever possible. This material may be suitable for approved landfill.

Dispose of only in accord with all regulations.

Precautions For content of open batteries: Wear protective equipment to prevent skin and eye

contamination and the inhalation of vapours. Work up wind or increase ventilation. For batteries: Ensure that no damage occurs to the batteries to prevent leakage of the

content.

7. Storage & Handling

Storage Store batteries in a cool, dry, well ventilation area. Keep away from heat, fire, sunlight

and ignition sources. Store batteries in their packaging. Unpacked batteries may short

circuit and generate heat.

Keep away from children. HandlingHandle batteries with care.

Do not recharge batteries, as this may cause leakage or rupture of the battery.

Do not solder or weld onto the battery. Do not mix with used, or other battery types.

If handling the contents of an open battery: Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of vapours/dusts.

Product Name: Maxlife Super Heavy Duty Battery

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

During normal use of a battery release of the contents of the battery does not occur.

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace	Ingredient	WES-TWA	WES-STEL
Exposure Stds	Manganese Dioxide	1mg/m³	data unavailable
	Zinc	10mg/m ³ (dust)	data unavailable
	Zinc chloride (fume)	1mg/m ³	data unavailable
	Graphite	3mg/m ³	data unavailable
	Carbon black	3mg/m ³	data unavailable



Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes

If handling the contents of an open battery, Protect eyes with goggles, safety glasses or full face mask. Avoid wearing contact lenses.

Skin If handling the contents of an open battery, avoid skin contact. Wear overalls, rubber

boots and impervious gloves. Nitrile or PVC gloves are recommended. Replace frequently. Gloves should be checked for tears or holes before use. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or

smoking.

Respiratory A respirator when airborne concentrations approach the WES (section 8). Use a

respirator with a particulate filter. If using a respirator, ensure that the cartridges are

correct for the potential air contamination and are in good working order.

WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearance metal cylinder shell containing electrolyte solution

Odour intact battery has no odour

pH 7-8
Vapour pressure no data
Viscosity no data
Boiling point no data
Volatile materials no data
Freezing / melting point >300°C

Solubility partly soluble in water

Specific gravity / density no data

Flash point non flammable

Danger of explosionno dataAuto-ignition temperatureno dataUpper & lower flammable limitsno data

Corrosiveness contents of the battery is corrosive to skin and eyes.

10. Stability & Reactivity

Stability Stable at room temperature and pressure. Stable during normal use.

Conditions to be avoided Keep from extreme heat and open flames. Do not puncture, crush or incinerate.

Prevent short circuits.

Do not attempt to recharge this battery.

Incompatible groups content of the battery: oxidising agents, flammable substances. Aluminium, acids.

zinc oxides, manganese oxides, carbon dioxide, carbon monoxide.

Product Name: Maxlife Super Heavy Duty Battery

Substance Specific none known

Incompatibility

Hazardous decomposition

products

Hazardous reactions none known



11. Toxicological Information

Summary

During normal use the battery are not considered harmful/toxic.

The following summary is for the contents of the battery.

IF SWALLOWED: Can cause burning and permanent damage to the mouth and throat.

IF IN EYES: cause permanent eye damage. IF ON SKIN: causes burns to the skin.

IF INHALED: if vapours are inhaled, these can cause respiratory irritation.

CHRONIC TOXICITY: prolonged or repeated contact with the contents of the battery may cause long term toxicity. Inhalation may impair brain function and show some developmental toxicity, i.e. it may affect foetus) and toxicity via breastmilk. (Manganese dioxide). Fine respirable dust of carbon black is suspected of causing cancer.

Supporting Data

Chronic

Acute Oral Using LD₅₀'s for ingredients, the calculated LD₅₀ (oral) for the mixture is between 2000

and 5,000 mg/kg. Data considered includes: Manganese Dioxide 3480mg/kg, Zinc

chloride: 200mg/kg (guinea pig) .

Dermal No evidence of dermal toxicity.

Inhaled Using LC₅₀'s for ingredients, the calculated LC₅₀ (inhalation, rat) for the mixture is

between 2 and 5 mg/L (dust/mist) ppm. Data considered includes: Manganese Dioxide LCL0: 0.5mg/L (dust/mist), Zinc: Acute exposure to zinc dust fumes can cause metal

fume fever in humans.

The mixture is considered to be corrosive to the eye, the pH of the contents is 12-13. Eye Skin The mixture is considered to be corrosive to the skin, the pH of the contents is 12-13.

Sensitisation No ingredient present at concentrations > 0.1% is considered a sensitizer.

Mutagenicity No ingredient present at concentrations > 0.1% is considered a mutagen.

Carcinogenicity Carbon black is classed as "possibly carcinogenic to humans (group 2A), which is

equivalent to 6.7B under HSNO. Carbon black is only carcinogenic as a respirable dust. This substance is enclosed in a battery casing and the carbon black is present in the solid form and hence no significant exposure to carbon black dust occurs during the use

Reproductive / The mixture is considered to be a reproductive or developmental toxicant, because Developmental

Manganese dioxide is known or suspected to have an effect on or via lactation.

Manganese dioxide dust has also been shown to affect offspring (developmental toxicity) **Systemic** The mixture is considered to be a known or presumed target organ toxicant, because

manganese dioxide is known or presumed to be a target organ toxicant. This product

may affect the brain.

Aggravation of None known.

existing conditions

12. **Ecological Data**

Summary

An intact battery is not considered harmful to the environment. However is exposed to the elements the housing may break down and release the contents of the battery. The contents is considered ecotoxic in the aquatic environment. Do not allow contents to reach waterways.

Supporting Data – for the contents of the battery

Aquatic Using EC₅₀'s for the contents of the battery: the calculated EC₅₀ for the mixture is < 1

> mg/L. Data considered includes: Zinc 0.14 mg/l (96h, Oncorhynchus mykiss), 0.07 mg/l (48hr, Daphnia magna), 0.03 mg/l (96hr, Selenastrum capricornutum), Zinc chloride: 0.066mg/L (96h, Oncorhynchus mykiss), 0.0499mg/L (48h, static, Moina irrasa),

> > Product Name: Maxlife Super Heavy Duty Battery

0.0447mg/L (96h, static Selenastrum capricornutum).

Bioaccumulation Zinc chloride is considered bioaccumulative.

Degradability

Soil EPA has not classified any of the ingredients as ecotoxic in the soil environment.

Terrestrial vertebrate The contents of the battery may be toxic towards terrestrial vertebrates. See acute

toxicity above.

Terrestrial invertebrate There is no evidence of toxicity towards terrestrial invertebrates.

Biocidal

Environmental effect levels No EELs are available for this mixture or ingredients



13. Disposal Considerations

Restrictions There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

Disposal method Disposal of this product must comply with the Hazardous Substances (Disposal) Notice

2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

(Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible

reuse or recycle packaging.

14. Transport Information

LAND TRANSPORT:

Not regulated for transport on land.

UN number:NAProper shipping name:NAClass(es)NAPacking group:NAPrecautions:Ecotoxic.Hazchem code:NA

AIR TRANSPORT:

IATA: Not restricted to IATA DGR according to special provision A123.

MARINE TRANSPORT:

IMO: Not restricted to IMDG CODE according to special provision A304.

15. Regulatory Information

Batteries are considered to be manufactured articles and are not, therefore, covered by the HSNO Act. Although they may contain hazardous substances, the item has an end use function wholly dependent on its shape and design, which does not involve the intentional release of any hazardous component. (from EPA New Zealand)

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code Approval: exempt - manufactured article Controls, EPA. www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

EC₅₀ Ecotoxic Concentration 50% − concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

EPA Environmental Protection Authority (New Zealand)

HAZCHEM Code Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

HSNO Hazardous Substances and New Organisms (Act and Regulations)

International Agency for Research on Cancer

LEL Lower Explosive Limit

LD₅₀ Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

LC₅₀ Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population

(usually rats)

NZIoC New Zealand Inventory of Chemicals

MSDS (SDS) Material Safety Data Sheet (or Safety Data Sheet)

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

TWA Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UEL Upper Explosive Limit
UN Number United Nations Number

Page 6 of 7

February 2020 Product Name: Maxlife Super Heavy Duty Battery



Product Name: Maxlife Super Heavy Duty Battery

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring

using procedures that gather air samples in the worker's breathing zone.

References

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: EU ECHA, ingredients SDS's, ChemIDplus

Review

Date Reason for review

March 2015 Not applicable – new SDS (Draft)

February 2020 5 yearly update

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.

